

Forecasting long-range atmospheric transport episodes of polychlorinated biphenyls using FLEXPART

Anne Karine Halse¹, Sabine Eckhardt¹ Martin Schlabach¹, Andreas Stohl¹, Knut Breivik^{1,2}

¹ Norwegian Institute for Air Research, Box 100, NO-2027 Kjeller, Norway

² University of Oslo, Department of Chemistry, Box 1033, NO-0315 Oslo, Norway

Abstract

The analysis of concentrations of persistent organic pollutants (POPs) in ambient air is costly and can only be done for a limited number of samples. It is thus beneficial to maximize the information content of the samples analyzed via a targeted observation strategy. Using polychlorinated biphenyls (PCBs) as an example, a forecasting system to predict and evaluate long-range atmospheric transport (LRAT) episodes of POPs at a remote site in southern Norway has been developed. The system uses the Lagrangian particle transport model FLEXPART, and can be used for triggering extra (“targeted”) sampling when LRAT episodes are predicted to occur. The system was evaluated by comparing targeted samples collected over 12 to 25 hours during individual LRAT episodes with monitoring samples regularly collected over one day per week throughout a year. Measured concentrations in all targeted samples were above the 75th percentile of the concentrations obtained from the regular monitoring program and included the highest measured values of all samples. This clearly demonstrates the success of the targeted sampling strategy.

1. Introduction

Background air measurements of persistent organic pollutants (POPs) within several existing monitoring programs (e.g. Tørseth et al., 2012; Wu et al., 2009) are typically conducted using active air sampling (AAS). However, the high cost associated with this type of sampling limits the spatial and temporal coverage of air measurements. Furthermore, sampling at many sites occurs only at fixed intervals (e.g. one day per week) without any *a priori* consideration of air mass transport (i.e., whether the air is likely to be polluted or not). While the current strategy is appropriate for the purpose of assessing long-term trends (years, decades), the intermittent sampling approach may not effectively capture key long-range atmospheric transport (LRAT) episodes (e.g. Yao et al., 2007), which are often associated with the highest POP concentrations (Eckhardt et al., 2007; Yao et al., 2007).

30 The objectives of this study were to (i) develop a forecast system using the FLEXPART model to predict
31 long-range atmospheric transport episodes of POPs using PCB-28 as a model compound, (ii) to evaluate
32 the capability of the forecast system to capture specific LRAT episodes at a background site in southern
33 Norway (Birkenes) through targeted sampling (i.e. when LRAT episodes are predicted), (iii) to assess
34 whether predicted LRAT episodes for PCB-28 coincide with elevated concentrations of additional PCBs,
35 and (iv) to identify source regions of PCBs during individual episodes.

36

37 **2. Material and Methods**

38 **2.1.1 The Birkenes observatory**

39 Sampling was carried out at the Birkenes observatory, which has been in operation since 1981. The station
40 is located in the southern part of Norway (N 58°23, E 08°15, 190 m.a.s.l), on top of a hill and is mainly
41 surrounded by forest. We refer to Eckhardt et al. (2009) for further details.

42 **2.1.2 Sampling**

43 Air sampling was carried out by use of high volume air sampling devices (DHA-80, Digital, Hegenau, CH),
44 where both particulate and gas phase samples were collected. The samplers consist of a glass fiber filter
45 (collecting particles), in combination with two polyurethane foam (PUF) plugs (7.5 cm x 4.5 cm), for
46 collection of the gaseous compounds. The glass fiber filters (weight: 53 g/m², thickness: 260 μm, particle
47 retention: 1,2 μm) were purchased from Whatman™ GF/C, GE Healthcare, Buckinghamshire, UK. Air was
48 pumped through the sampling material. For regular monitoring samples collected once per week, the
49 pump was set to sample ~770 m³ (0.5 m³/minute) of air for 24 hours of sampling (Eckhardt et al., 2009).
50 The targeted air samples were collected by use of a similar high-volume air sampling device (DHA-80,
51 Digital), using a different pump (SAH 155, Elmo Rietschle, Bad Neustadt, Germany). This included both an
52 on-line control of the sampling system and the possibility to apply a higher flow rate to achieve shorter
53 sampling periods, since LRAT episodes are often shorter than a day. The sampling volumes for the targeted
54 LRAT samples ranged from 395 to 1443 m³ (average 0.8, range 0.6-0.9 m³/minute) and were collected
55 over 12 to 25 hours. After sampling was completed, the exposed PUF samples were sealed in a gas tight
56 container and glass fiber filters were wrapped in alumina foil and sealed.

57 **2.1.3 Clean-up and analysis**

58 Prior to sampling, the glass fiber filters were heated to 450 °C for 8 hours and wrapped in alumina foil.
59 PUF plugs were pre-extracted with acetone and toluene for 8 hours using a Soxhlet extraction system and

60 dried under vacuum in desiccators (Eckhardt et al., 2009). After sampling was completed, a mixture of
61 ^{13}C -isotope labeled internal standard of PCBs was added to the sample material (both filter and PUFs)
62 prior to extraction. Samples were extracted via Soxhlet extraction using *n*-hexane/diethyl ether 9:1 as an
63 extraction solvent (Eckhardt et al., 2009). All extracts were pre-concentrated to approximately 2 mL and
64 treated with sulfuric acid to remove matrix related components. The organic phase was further cleaned
65 up using a silica column and eluted with *n*-hexane/diethyl ether. The final extracts were reduced in volume
66 to approximately 0.1 mL using nitrogen followed by the addition of a recovery standard (Eckhardt et al.,
67 2009). An Agilent 6890 gas chromatograph coupled to a high resolution Waters AutoSpec mass
68 spectrometer in an electron impact mode was used for quantification and identification of the target
69 compounds. The gas chromatograph conditions are given elsewhere (e.g. Eckhardt et al., 2009).

70

71 **2.2 FLEXPART model**

72 The atmospheric transport of PCB-28 was simulated by use of the Lagrangian particle dispersion model
73 FLEXPART (Stohl et al., 2005; Stohl et al., 1998). The main purpose for FLEXPART model simulations was
74 to calculate PCB-28 concentrations at the measurement station and identify the source regions of PCB-
75 28. The model calculates the trajectories of so-called tracer particles and accounts for turbulence,
76 convection, deposition and atmospheric reaction with hydroxyl (OH) radicals (Eckhardt et al., 2009).

77 FLEXPART was run in backward mode for this study in order to identify possible source regions influencing
78 the measurement site during an air pollution episode (Eckhardt et al., 2007; Seibert and Frank, 2004).
79 Following an earlier study for Birkenes (Eckhardt et al., 2009), PCB-28 was chosen as our model compound.
80 We used the maximum emission scenario derived by Breivik et al. (2007) as model input. Physical-chemical
81 properties for PCB-28 were adapted from Li et al. (2003) and the atmospheric reaction rate taken from
82 Anderson and Hites (1996) as further detailed in Eckhardt et al. (2009).

83 FLEXPART was run daily using meteorological forecast data to predict airborne concentration of PCB-28
84 for the following day (further referred to as FLEXPART-forecast – *FLEXPART-f*). The FLEXPART run was
85 initialized at the coordinates of the measurement site and at the future time and was then run backward
86 in time incorporating first forecast meteorological data and, for past periods for which such data were
87 already available at the time of the model calculations, analysis data. Predictions using *FLEXPART-f* began
88 in December 2008. By the end of 2010, the upper 95% percentile for simulated concentrations of PCB-28
89 (5.7 pg/m^3) was determined and selected as a threshold limit for targeted sampling of predicted LRAT
90 episodes. During 2011, upcoming LRAT episodes were identified one day ahead by *FLEXPART-f* as
91 predicted concentrations exceeding the threshold of 5.7 pg/m^3 .

92 After all targeted sampling was completed, FLEXPART was run again for dates in which sampling occurred
93 but using meteorological analysis data (these runs will be referred to as FLEXPART-retrospective –
94 *FLEXPART-r*). In *FLEXPART-f* 40 000 particles were released over a 24 hour interval, and in *FLEXPART-r* 100
95 000 particles were released over the exact interval of the measurement, from the receptor site (Birkenes)
96 and followed backwards in time for 20 days in order to calculate emission sensitivities (ES) (Seibert and
97 Frank, 2004; Stohl et al., 2003; Stohl et al., 2005). A larger number of particles were released for the
98 *FLEXPART-r* runs for more accurate determination of source regions during the episodes which were
99 sampled. The ES (unit nanoseconds) provides information about the residence time of an air mass within
100 a grid cell and uptake of emissions was facilitated in the so-called footprint layer (0-100 m above ground)
101 (Eckhardt et al., 2009). Multiplying the footprint ES value by emission fluxes from the PCB-28 emission
102 inventory (Breivik et al., 2007) yields the geographical distribution of sources contributing to the simulated
103 concentrations at the measurement site. Spatial integration of all contributions then gives the simulated
104 concentration at the measurement site.

105 For the forecast system (*FLEXPART-f*), FLEXPART used meteorological forecast data taken every three
106 hours (26 model levels and resolution of 1×1 globally) from the Global Forecast System (GFS) model of the
107 National Centers for Environmental Prediction (NCEP) to predict the concentration of PCB-28 one day
108 ahead. For the selected episodes which were subject to targeted sampling and analysis, FLEXPART
109 (*FLEXPART-r*) was run for retrospective simulations driven by operational analysis from the European
110 Centre for Medium-Range Weather Forecasts (ECMWF, 1995), with 1°×1° resolution and 91 model levels.
111 Analyses at 00:00, 06:00, 12:00 and 18:00 UTC, and 3-h forecasts at 03:00, 09:00, 15:00 and 21:00 UTC
112 were used.

113 **3. Results and Discussion**

114 **3.1. Annual averages and concentrations during the predicted episodes**

115 Samples from targeted sampling (based on model results of *FLEXPART-f*) during three predicted LRAT
116 episodes (E) in 2011, which occurred in January (E1), February (E2) and late September/early October (E3a
117 ,b, c, d, e), were analyzed (Table 1). An overview of predicted and measured concentrations is presented
118 in Table A.1 in Appendix.

119 Figure 1 compares the modeled *FLEXPART-r* concentrations of PCB-28, and selected PCBs measured during
120 the individual episodes (n=7, colored dots) with annual results obtained through the regular monitoring
121 program (n=52). We show results for *FLEXPART-r* modeled PCB-28 (a) and measured concentrations for
122 seven PCBs (PCB-52,-101,-118,-138,-153,-180) (b-h). In Figure 1, the median and the percentiles were

123 estimated based on annual results for the AAS sampler. To further facilitate interpretation of results, Table
124 A.1 tabulates the predicted and measured concentrations (pg/m^3) during each sampled episode. Table
125 A.2 presents the annual mean and standard deviation (SD) based on results from the regular monitoring
126 program in 2011 ($n=52$) and compares concentrations measured during each episode with the annual
127 mean.

128 There are major uncertainties in the exact magnitude of PCB emissions with different emission scenarios
129 varying by several orders of magnitude (Breivik et al., 2007 and references therein). Independent model
130 evaluations using this data have therefore experienced difficulties in accurately reproducing the exact
131 magnitude of observed concentrations (e.g. Gong et al., 2007; Macleod et al., 2005; Wania and Su, 2004).
132 For all episodes, we start by noting that the model overestimated measured concentrations of PCB-28
133 during the episodes by a factor of 4.2 on average, ranging from 1.7 (E3e) to 7.7 (E2). This was anticipated
134 based on past model evaluations using FLEXPART (Eckhardt et al., 2009; Halse et al., 2011) and mainly
135 attributed to uncertainties in the maximum emission scenario used as model input (Breivik et al., 2007).
136 Despite this uncertainty, the model was clearly successful in singling out LRAT episodes of PCB-28 as all
137 targeted samples exceeded the 75 percentile of the regular monitoring program (Figure 1b). The
138 measurements were elevated, ranging from mean plus 0.8 standard deviations (E1) up to mean plus 6.4
139 standard deviations (E3e) (Table A.2), with two samples (E3e and E3c) containing the highest
140 concentrations of the 52 samples collected as part of the monitoring program. However, the ranking of
141 predicted and observed concentrations of PCB-28 did not fully match, with predictions for PCB-28
142 decreasing from $E3c > E2 > E3b > E3d > E3a \approx E3e > E1$ and observations declining from $E3e > E3c > E3b >$
143 $E3d > E3a > E2 > E1$ (Table A.1). Nevertheless, the overall results indicate that there is a fairly good
144 understanding of major source regions leading to elevated concentrations of PCB-28 at Birkenes.

145 An obvious question to follow is whether the model predictions may work as a suitable surrogate for PCBs
146 other than PCB-28? For all other PCB congeners, each episodically collected sample was above the 75
147 percentile (Figure 1c-h). Furthermore, the measurements of $\Sigma_7\text{PCBs}$ were elevated by 0.7 (E1) to 6.9 (E3e)
148 SDs (Table A.2) above the annual mean, with all congeners being elevated by more than two SDs for the
149 five consecutive samples collected during autumn (E3). As the ranking of observed concentrations from
150 high to low are identical for each PCB congener in all targeted samples ($E3e > E3c > E3b > E3d > E3a > E2$
151 $> E1$), we conclude that PCB-28 serves as a suitable surrogate to identify probable LRAT episodes for the
152 other congeners included. This would imply that major source regions affecting concentrations of these
153 PCBs are likely to be similar.

154 3.2. Source regions predicted using backwards simulation

155 Figures 2a and 2b shows the corresponding *FLEXPART-r* emission contribution (EC) maps for the episodes
156 with highest modeled (E3c) and measured (E3e) concentrations of PCB-28 in air at Birkenes, respectively.
157 Similarly, Figures A.6 and A.8 in the Appendix show the *FLEXPART-r* footprint emission sensitivity (ES)
158 maps for these two episodes. Additional maps based on annual results as well as the other individual
159 episodes are included in the Appendix (Figures A.1-A.8).

160 While E3c had the highest modeled (*FLEXPART-r*) concentration of PCB-28, the highest measured
161 concentration was found for E3e (Table A.1). This may reflect inaccuracies in the spatial emission pattern
162 used as model input. In other words, the emissions in western parts of Europe highlighted in Figure 2b
163 (e.g. UK and/or France) might be underestimated in the emission inventory compared to those regions in
164 more central parts of mainland Europe which are highlighted in Figure 2a. A study done by Eckhardt et al.
165 (2009) revealed that the dominating regions for PCB-28 affecting Birkenes were Eastern and Central
166 Europe together with the UK and Ireland. Although the data set of targeted samples is too limited to infer
167 any reliable conclusions (as e.g. atmospheric loss processes occurring en route could have been more
168 efficient than predicted by the model in the case of E3c, relatively to E3e), it illustrates how a combined
169 modeling and monitoring approach has the potential to better constrain our understanding of how major
170 source regions are affecting concentrations of PCBs at a background site.

171 4. Conclusions

172 Trajectories have been widely used to interpret air measurement of various POPs and other pollutants.
173 However, few studies have performed targeted air sampling of organic contaminants from suspected
174 source regions as triggered by real-time meteorological forecast models (Yao et al., 2007). To the best of
175 our knowledge, our study represents the first attempt to both (i) use model predictions driven by *a priori*
176 information on emissions of POPs to trigger air sampling as well as (ii) retrospectively evaluate the source
177 regions for measurements collected during predicted episodes. The *FLEXPART-f* model was clearly
178 successful in identifying LRAT episodes for both PCB-28 and other PCBs as the measured concentration of
179 PCB-28 in all seven targeted samples was above the 75 percentile with two samples exceeding
180 concentrations measured in the 52 samples collected as part of the regular monitoring program. The
181 *FLEXPART-r* model fails to accurately reproduce the magnitude of PCB-28 concentrations during individual
182 episodes, but this can be mainly attributed to uncertainties in the absolute emission rates of PCB-28 used
183 to drive simulations. We conclude that forecasting of pollution episodes has the potential to add value to
184 relevant monitoring efforts which are normally collecting active air samples at fixed intervals in a non-

185 continuous manner. Observations targeted at strong pollution episodes (as in this paper) or on transport
186 from specific source regions with highly uncertain emissions (as could be done in a very similar forecasting
187 framework) could significantly enhance our understanding of POP sources. However, in order to obtain
188 more confidence in the forecast system and predicted source-receptor relationships (*FLEXPART-r*), the
189 number of targeted samples which are collected and substances which are predicted and analyzed need
190 to be increased.

191 **Acknowledgements**

192 This study was financed by the Research Council of Norway (183437/S30). We would also like to thank
193 the Norwegian Climate and Pollution Agency for financing the POPs monitoring program at Birkenes,
194 Olav Lien for support with the sampling, and Nick Warner for comments on this manuscript.

195 5. References

- 196 Anderson, P.N., Hites, R.A., 1996, OH radical reactions: The major removal pathway for polychlorinated
197 biphenyls from the atmosphere. *Environ. Sci. Technol.* 30, 1756-1763.
- 198 Breivik, K., Sweetman, A., Pacyna, J.M., Jones, K.C., 2007, Towards a global historical emission inventory
199 for selected PCB congeners - A mass balance approach-3. An update. *Science of the Total*
200 *Environment* 377, 296-307.
- 201 Eckhardt, S., Breivik, K., Li, Y.F., Mano, S., Stohl, A., 2009, Source regions of some persistent organic
202 pollutants measured in the atmosphere at Birkenes, Norway. *Atmospheric Chemistry and*
203 *Physics* 9, 6597-6610.
- 204 Eckhardt, S., Breivik, K., Mano, S., Stohl, A., 2007, Record high peaks in PCB concentrations in the Arctic
205 atmosphere due to long-range transport of biomass burning emissions. *Atmospheric Chemistry*
206 *and Physics* 7, 4527-4536.
- 207 ECMWF, E.C.f.M.-R.W.F. 1995. User guide to ECMWF products 2.1 (Reading, Meteorological Bulletin).
- 208 Gong, S.L., Huang, P., Zhao, T.L., Sahsuvar, L., Barrie, L.A., Kaminski, J.W., Li, Y.F., Niu, T., 2007,
209 GEM/POPs: a global 3-D dynamic model for semi-volatile persistent organic pollutants - Part 1:
210 Model description and evaluations of air concentrations. *Atmospheric Chemistry and Physics* 7,
211 4001-4013.
- 212 Halse, A.K., Schlabach, M., Eckhardt, S., Sweetman, A., Jones, K.C., Breivik, K., 2011, Spatial variability of
213 POPs in European background air. *Atmospheric Chemistry and Physics* 11, 1549-1564.
- 214 Li, N.Q., Wania, F., Lei, Y.D., Daly, G.L., 2003, A comprehensive and critical compilation, evaluation, and
215 selection of physical-chemical property data for selected polychlorinated biphenyls. *Journal of*
216 *Physical and Chemical Reference Data* 32, 1545-1590.
- 217 Macleod, M., Riley, W.J., McKone, T.E., 2005, Assessing the influence of climate variability on
218 atmospheric concentrations of polychlorinated biphenyls using a global-scale mass balance
219 model (BETR-global). *Environ. Sci. Technol.* 39, 6749-6756.
- 220 Seibert, P., Frank, A., 2004, Source-receptor matrix calculation with a Lagrangian particle dispersion
221 model in backward mode. *Atmospheric Chemistry and Physics* 4, 51-63.
- 222 Stohl, A., Forster, C., Eckhardt, S., Spichtinger, N., Huntrieser, H., Heland, J., Schlager, H., Wilhelm, S.,
223 Arnold, F., Cooper, O., 2003, A backward modeling study of intercontinental pollution transport
224 using aircraft measurements. *J. Geophys. Res.-Atmos.* 108, 18.
- 225 Stohl, A., Forster, C., Frank, A., Seibert, P., Wotawa, G., 2005, Technical note: The Lagrangian particle
226 dispersion model FLEXPART version 6.2. *Atmospheric Chemistry and Physics* 5, 2461-2474.
- 227 Stohl, A., Hittenberger, M., Wotawa, G., 1998, Validation of the Lagrangian particle dispersion model
228 FLEXPART against large-scale tracer experiment data. *Atmospheric Environment* 32, 4245-4264.
- 229 Tørseth, K., Aas, W., Breivik, K., Fjæraa, A.M., Fiebig, M., Hjellbrekke, A.G., Lund Myhre, C., Solberg, S.,
230 Yttri, K.E., 2012, Introduction to the European Monitoring and Evaluation Programme (EMEP)
231 and observed atmospheric composition change during 1972-2009. *Atmospheric Chemistry and*
232 *Physics* 12, 5447-5481.
- 233 Wania, F., Su, Y.S., 2004, Quantifying the global fractionation of polychlorinated biphenyls. *Ambio* 33,
234 161-168.
- 235 Wu, R., Backus, S., Basu, I., Blanchard, P., Brice, K., Dryfhout-Clark, H., Fowlie, P., Hulting, M., Hites, R.,
236 2009, Findings from quality assurance activities in the Integrated Atmospheric Deposition
237 Network. *J. Environ. Monit.* 11, 277-296.
- 238 Yao, Y., Harner, T., Ma, J.M., Tuduri, L., Blanchard, P., 2007, Sources and occurrence of dacthal in the
239 Canadian atmosphere. *Environ. Sci. Technol.* 41, 688-694.
- 240
- 241

242 Table 1: Sampling times for targeted samples collected during predicted episodes in 2011.

Episode	Start date	Start time	End date	End time
E1	06.01	11:50	07.01	23:49
E2	24.02	17:29	25.02	05:49
E3a	29.09	08:05	29.09	21:10
E3b	29.09	21:15	30.09	15:30
E3c	30.09	15:30	01.10	05:35
E3d	01.10	05:38	02.10	07:04
E3e	02.10	07:08	02.10	18:49

243

244 **Figure Captions:**

245

246 Figure 1: Modeled (*FLEXPART-r*) PCB-28 (a) and measured PCB concentrations (b-h) in units of pg/m^3 , for
247 both the annual sampling program and the targeted samples. The box and whisker plots show the annual
248 results (2011) for Birkenes, Southern Norway based on weekly samples. The line shows the median, while
249 the box and whiskers delineates the 25 and 75 percentiles and the 5 and 95 percentiles, respectively.
250 Targeted samples are represented by colored dots.

251

252 Figure 2: Maps of *FLEXPART-r* EC (emission contributions, $1\text{E}-12$ [pg/m^3]) for PCB-28 for the episodes
253 with highest predicted (E3c) (a) and measured (E3e) (b) concentrations at Birkenes during 2011.

254




Figure 1




Figure 2